



The First in Synthetics®

AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid

Reserve protection for heavily loaded gears

AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid is engineered to deliver upgraded performance for hard-working and performance ATVs and UTVs. Its outstanding severe-service formulation allows you to confidently and safely push your machine to the limit, whether tackling tough chores around your property or riding aggressively on the trail. AMSOIL synthetic technology protects heavily loaded gears against wear. AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid is Warranty Secure™ and will not void your ATV or UTV warranty. It is a cost-effective, high-performance alternative to OEM fluids.

Severe-Service Wear Protection

Many enthusiasts modify their ATVs or UTVs with roof and door panels, skid plates, a winch, a plow or other accessories that add weight and increase the severity of operation. Aggressive riding and tough terrain place additional stress on the transmission and gears. Extreme pressures and high torque generated during severe-duty operation cause oils formulated for standard service to lose viscosity due to shear, placing components at risk of wear.

AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid boasts outstanding film strength and resists extreme pressures. It protects heavily loaded, high-torque gears and bearings against wear in the most severe operating conditions.

Superior Extreme-Temperature Performance

High heat generated from towing and hauling can cause lubricants to break down, leading to harmful deposits and wear. AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid cools critical components and resists the effects of extreme heat to deliver reliable protection in severe service. Its synthetic technology helps it remain fluid in cold weather.



API GL-5

- **Protection** when performing demanding chores and tackling tough terrain
- **Protects** heavily loaded, high-torque gears
- **Superior** all-weather protection



TYPICAL TECHNICAL PROPERTIES

AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid (AUDT)

Kinematic Viscosity @ 100°C, cSt (ASTM D445)	15.6
Kinematic Viscosity @ 40°C, cSt (ASTM D445)	120.4
Viscosity Index (ASTM D2270)	136
Flash Point, °C (°F) (ASTM D92)	210 (410)
Fire Point, °C (°F) (ASTM D92)	220 (428)
Pour Point, °C (°F) (ASTM D97)	-43 (-45)
Four-Ball Wear Test (ASTM D4172) Para 3 (150°C, 1800 rpm, 40 kg, 1 hr)	0.46
Foam (ASTM D892) Sequence I, II & III	0/0/0

APPLICATIONS*

Use in ATV and UTV transmissions and differentials, including those made by Honda, Yamaha, Kawasaki, Can-Am and Suzuki.

SERVICE LIFE

Follow the original equipment manufacturer's oil change recommendation.

WARRANTY SECURE™

AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid is Warranty Secure, keeping your factory warranty intact. AMSOIL Synthetic ATV/UTV Transmission & Differential Fluid is a high-performance replacement for vehicle manufacturer-branded products and is also backed by the AMSOIL Limited Warranty (G1363). For details, visit [AMSOIL.com/warrantysecure](https://www.amsoil.com/warrantysecure).

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended applications and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available online at [AMSOIL.com](https://www.amsoil.com) or upon request at (715) 392-7101. **Keep Out of Reach of Children.** Recycle used oil and bottle.



*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.